
## Brass Ball Valve -EN331 British Gas Approved



Nickel Plated Brass Body, Screwed BSPP Female, Full Bore, Yellow PVC Coated Steel Lever



| Pressure/Temperature Ratings |                |      |  |
|------------------------------|----------------|------|--|
| Pressure                     | 1/4" to 1/2"   | PN40 |  |
|                              | 3/4" to 1"     | PN32 |  |
|                              | 1¼" to 2½"     | PN25 |  |
|                              | 3" - 4"        | PN16 |  |
| Temperature Range            | -20°C to 110°C |      |  |

| Material List |                     |
|---------------|---------------------|
| Body          | Brass Nickel Plated |
| Ball          | Brass Nickel Plated |
| Stem          | Brass               |
| Stem O-Rings  | NBR                 |
| Lever         | Steel PVC Coated    |

| Dimensions |     |     |      |  |
|------------|-----|-----|------|--|
| DN         | Н   | L   | Kg   |  |
| 1/4"       | 48  | 48  | 0.08 |  |
| 3/8"       | 48  | 48  | 0.1  |  |
| 1/2"       | 55  | 55  | 0.16 |  |
| 3/4"       | 66  | 66  | 0.27 |  |
| 1"         | 70  | 70  | 0.41 |  |
| 11/4"      | 83  | 83  | 0.62 |  |
| 11/2"      | 93  | 93  | 0.87 |  |
| 2"         | 102 | 102 | 1.5  |  |
| 21/2"      | 143 | 143 | 2.03 |  |
| 3"         | 153 | 153 | 3.72 |  |
| 4"         | 187 | 187 | 5.98 |  |