

## Brass Ball Valve with Extended Neck - ISO Top

ISO 5211 Connection for Direct Mount, BSPP Female, For use with Thermal Insulation.

Note: Neck is non-rotating when handle turned.

### Pressure/Temperature Ratings

Pressure	PN40
Temperature Range	-10°C to 100°C

### Dimensions

DN	S	Ø	P	H	E	Q	ISO	Nm	Kg
1/2"	56	15	14	89	8	11	F03	4	0.36
3/4"	68	20	16	92	8	11	F03	4	0.56
1"	78	25	17	98	8	11	F03	5	0.98
1 1/4"	90	32	18	108	10	11	F05	5	1.44
1 1/2"	100	39	19	114	10	11	F05	6	1.81
2"	115	48	21	131	10	11	F05	7	2.89

### Material List

Body	Brass, Nickel Plated
Ball	Brass, Chrome Plated
Seat O-ring*	NBR
Mounting Plate	Brass, Nickel Plated
Packing Nut	Brass
Gland Nut	Brass
Thrust Washer	PTFE
Stem Washer	PTFE
Stem	Brass
Stem O-ring	NBR
Seat	PTFE
Body Connector	Brass, Nickel Plated
Spacer	Brass

\*Seat O-ring absent on 1/2"

