

LV 4530
LV 4531

Brass Ball Valve - Three Way Divertor, T-Port/L-Port

ISO 5211 Connections for Direct Mount, Nickel Plated Body, Screwed BSPP Female Ends, Full Bore, Top Lever Operated

Pressure/Temperature Ratings

Max Pressure	PN25
Temperature Range	-10°C to 100°C

Material List

Body	Brass, Nickel Plated
Ball	Brass, Chrome Plated
Seat O-ring*	NBR
Mounting Plate	Brass, Nickel Plated
Packing Nut	Brass
Gland Nut	Brass
Thrust Washer	PTFE
Stem Washer	PTFE
Stem	Brass
Stem O-ring	NBR
Seat	PTFE
Spacer	Brass

*Seat O-ring absent on 1/2"

Dimensions

DN	Ø1	Ø2	S	P	H	E	Q	ISO	Nm	Kg
1/2"	10	10	56	14	48	8	11	F03	4	0.41
3/4"	15	15	68	16	52	8	11	F03	4	0.51
1"	20	20	78	17	56	8	11	F03	5	0.73
1 1/4"	25	25	90	18	68	10	11	F05	5	1.18
1 1/2"	32	32	100	19	73	10	11	F05	6	1.72
2"	40	40	115	21	79	10	11	F05	7	2.6
3"	68	68	180	25	104	12	11	F05	18	7.36

