

## ISO B12 Couplings

### Info / Accessories



Designed and manufactured in Sheffield by PCL. This range of couplings offers excellent flow characteristics for industrial applications where this adaptor profile is required.

### Key Product Benefits

- Offers enhanced tool efficiency
- Steel construction with corrosive resistant finish
- Steel shoulder prevents accidental disconnection

### Specifications

Nominal bore	5.5 mm	
Flow rate @ 6bar	1100 l/min @ 0.5 bar p.d.	
Maximum Working Pressure	500 lbf/in <sup>2</sup>	35 bar
Interchangeability	Rectus 23/24	
	Cejn 310	
	Norgren Dynaquip DC3	
	Hanson 3000	
	US-MIL-C 4109 1/4"	
	Norgren 237	

### Product Options

Part No.	Description	Thread Type	Thread Size
AC75CM	ISO B12 Coupling	Male	R 1/4
AC75EM	ISO B12 Coupling	Male	R 3/8
AC75JM	ISO B12 Coupling	Male	R 1/2
AC75CF	ISO B12 Coupling	Female	Rp 1/4
AC75EF	ISO B12 Coupling	Female	Rp 3/8
AC75JF	ISO B12 Coupling	Female	Rp 1/2
AC7506	ISO B12 Coupling	Hose Tailpiece	6mm
AC7508	ISO B12 Coupling	Hose Tailpiece	8mm
AC7510	ISO B12 Coupling	Hose Tailpiece	10mm
AC7513	ISO B12 Coupling	Hose Tailpiece	13mm