

## KF Couplings

Info / Accessories



This range of couplings offers excellent flow characteristics ideal for portable air tool and industrial applications where this adaptor profile is required. Designed and manufactured in Sheffield by PCL.

### Key Product Benefits

- Offers enhanced tool efficiency
- Steel construction with corrosive resistant finish
- Steel shoulder prevents accidental disconnection

### Specifications

Nominal bore	7.6 mm	
Flow rate @ 6bar	2100 l/min @ 0.5 bar p.d.	
Maximum Working Pressure	500 lbf/in <sup>2</sup>	35 bar
Interchangeability	Rectus 13	
	Nitto Kohki 200	
	Cejn 314/315	

### Product Options

Part No.	Description	Thread Type	Thread Size
AC78CM	KF Coupling	Male	R 1/4
AC78EM	KF Coupling	Male	R 3/8
AC78JM	KF Coupling	Male	R 1/2
AC78CF	KF Coupling	Female	Rp 1/4
AC78EF	KF Coupling	Female	Rp 3/8
AC78JF	KF Coupling	Female	Rp 1/2
AC7806	KF Coupling	Hose Tailpiece	6mm
AC7808	KF Coupling	Hose Tailpiece	8mm
AC7810	KF Coupling	Hose Tailpiece	10mm
AC7813	KF Coupling	Hose Tailpiece	13mm