



Technical Description

Universal brass coupling with European standard industrial profile.
Coupling system with single-hand operation and standard-valve. Small mass size. The ergonomic sleeve design prevents dirt on the valve body.

Working Temperature*

-20°C up to +100°C (NBR) depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

Other designs in series 26

The following other designs can be found from page:

- Stainless Steel P. 202
- Safety Self-Venting P. 292



Working Pressure**

35 bar
** maximum static working pressure with safety factor 4 to 1.

35 bar

Features

- Series 26 plugs in brass
- Series 25 steel plugs recommended for oscillating forces

Material





Coupling: Brass
Plug: Brass
Seals: NBR


Coupling: Brass
Plug: Brass
Seals: NBR

Interchangeability

- Rectus 25
- Rectus 1600/1625
- Cejn 320
- JWL 520 + JWL 530
- various German Products


Flow diagrams





Male Thread

Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
G 1/8	22		43	9		25			blank	26KAAW10MPX
G 1/8	22		43	9		25			nickel plated	26KAAW10MPN
G 1/4	22		39	9		25			blank	26KAAW13MPX
G 1/4	22		39	9		25			nickel plated	26KAAW13MPN
G 3/8	22		41	9		25			blank	26KAAW17MPX
G 3/8	22		41	9		25			nickel plated	26KAAW17MPN
G 1/2	22		44	12		25			blank	26KAAW21MPX
G 1/2	22		44	12		25			nickel plated	26KAAW21MPN
G 1/2	24		44	12		25			blank	26KAAW21MPXS_36
G 1/2	24		44	12		25			nickel plated	26KAAW21MPNS_09
M 14 x 1,5	22		42	10		25			blank	26KAAD14MPX
M 14 x 1,5	22		42	10		25			nickel plated	26KAAD14MPN
M 16 x 1,5	22		43	11		25			blank	26KAAD16MPX
M 16 x 1,5	22		43	11		25			nickel plated	26KAAD16MPN
M 18 x 1,5	22		43	11		25			blank	26KAAD18MPX
M 18 x 1,5	22		43	11		25			nickel plated	26KAAD18MPN







Female Thread

G 1/4	22		41	9		25			blank	26KAIW13MPX
G 1/4	22		41	9		25			nickel plated	26KAIW13MPN
G 3/8	22		41	9		25			blank	26KAIW17MPX
G 3/8	22		41	9		25			nickel plated	26KAIW17MPN
G 1/2	24		44	10		25			blank	26KAIW21MPX
G 1/2	24		44	10		25			nickel plated	26KAIW21MPN
M 14 x 1,5	22		44	9		25			blank	26KAIM14MPX
M 14 x 1,5	22		44	9		25			nickel plated	26KAIM14MPN
M 16 x 1,5	22		44	9		25			blank	26KAIM16MPX
M 16 x 1,5	22		44	9		25			nickel plated	26KAIM16MPN
M 18 x 1,5	22		44	9		25			blank	26KAIM18MPX
M 18 x 1,5	22		44	9		25			nickel plated	26KAIM18MPN



Couplings – with valve

Series 26KA

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number	
 <p>Hose Barb</p>	6 mm	21		58	25		25			blank	26KATF06MPX	
	6 mm	21		58	25		25			nickel plated	26KATF06MPN	
	8 mm	21		58	25		25			blank	26KATF08MPX	
	8 mm	21		58	25		25			nickel plated	26KATF08MPN	
	9 mm	21		58	25		25			blank	26KATF09MPX	
	9 mm	21		58	25		25			nickel plated	26KATF09MPN	
	10 mm	21		58	25		25			blank	26KATF10MPX	
	10 mm	21		58	25		25			nickel plated	26KATF10MPN	
	13 mm	21		58	25		25			blank	26KATF13MPX	
	13 mm	21		58	25		25			nickel plated	26KATF13MPN	
	6 mm Parker	21		58	20,5		25				blank	26KATP06MPX
	6 mm Parker	21		58	20,5		25				nickel plated	26KATP06MPN
	10 mm Parker	21		58	24		25				blank	26KATP10MPX
	10 mm Parker	21		58	24		25				nickel plated	26KATP10MPN
	13 mm Parker	21		58	28		25				blank	26KATP13MPX
	13 mm Parker	21		58	28		25				nickel plated	26KATP13MPN
 <p>with Plastic Hose Connection</p>	4 x 6 mm	21		58	7	6	25		M 10 x 1	blank	26KAKO06MPX	
	4 x 6 mm	21		58	7	6	25		M 10 x 1	nickel plated	26KAKO06MPN	
	6 x 8 mm	21		45	7	6	25		M 12 x 1	blank	26KAKO08MPX	
	6 x 8 mm	21		45	7	6	25		M 12 x 1	nickel plated	26KAKO08MPN	
	8 x 10 mm	21		49	9	8	25		M 16 x 1	blank	26KAKO10MPX	
	8 x 10 mm	21		49	9	8	25		M 16 x 1	nickel plated	26KAKO10MPN	
	9 x 12 mm	21		49	9	8	25		M 16 x 1	blank	26KAKO12MPX	
	9 x 12 mm	21		49	9	8	25		M 16 x 1	nickel plated	26KAKO12MPN	
 <p>Panel Mount with Hose Barb</p>	6 mm	21	17	60	17	10	25	4	M 12 x 1	blank	26KATS06MPX	
	6 mm	21	17	60	17	10	25	4	M 12 x 1	nickel plated	26KATS06MPN	
	8 mm	21	17	63	17	14	25	4	M 12 x 1	blank	26KATS08MPX	
	8 mm	21	17	63	17	14	25	4	M 12 x 1	nickel plated	26KATS08MPN	
	10 mm	21	17	72	25	14	25	4	G 1/4	blank	26KATS10MPX	
	10 mm	21	17	72	25	14	25	4	G 1/4	nickel plated	26KATS10MPN	
 <p>Plastic Hose Connection with Spring Guard</p>	6 x 8 mm	21		132	7	6	25		M 12 x 1	blank	26KAKK08MPX	
	6 x 8 mm	21		132	7	6	25		M 12 x 1	nickel plated	26KAKK08MPN	
	8 x 10 mm	21		143	9	8	25		M 16 x 1	blank	26KAKK10MPX	
	8 x 10 mm	21		143	9	8	25		M 16 x 1	nickel plated	26KAKK10MPN	
	9 x 12 mm	21		150	9	8	25		M 16 x 1	blank	26KAKK12MPX	
	9 x 12 mm	21		150	9	8	25		M 16 x 1	nickel plated	26KAKK12MPN	