

ZF Couplings

Info / Accessories



This range of couplings offers superior flow characteristics for industries with exceptional air flow applications. Designed and manufactured in Sheffield by PCL.

Key Product Benefits

- Secure, single locking action
- Larger bore for increased flow rates
- Hard wearing steel construction with corrosive resistant finish

Specifications

Nominal bore	10.5 mm	
Flow rate @ 6bar	3000 l/min @ 0.5 bar p.d.	
Maximum Working Pressure	500 lbf/in ²	35 bar
Interchangeability	Rectus 27	
	Cejn 410	
	Legris 27	
	Schrader InterCheck 55	



Product Options

Part No.	Description	Thread Type		Thread Size	
AC81CM	ZF Coupling	Male		R 1/4	
AC81EM	ZF Coupling	Male		R 3/8	
AC81JM	ZF Coupling	Male		R 1/2	
AC81LM	ZF Coupling	Male		R 3/4	
AC81CF	ZF Coupling	Female		Rp 1/4	
AC81EF	ZF Coupling	Female		Rp 3/8	
AC81JF	ZF Coupling	Female		Rp 1/2	
AC81LF	ZF Coupling	Female		Rp 3/4	
AC8108	ZF Coupling	Hose Tailpiece		8mm	
AC8110	ZF Coupling	Hose Tailpiece		10mm	
AC8113	ZF Coupling	Hose Tailpiece		13mm	
AC8116	ZF Coupling	Hose Tailpiece		16mm	
AC8119	ZF Coupling	Hose Tailpiece		19mm	