

M2E series 125~250

REFRIGERATION COMPRESSED AIR DRYER



Design condition

Working pressure: 0.7MPa	0.4	0.5	0.6	0.7	0.8	0.9	1.0
A. Correction factor	0.63	0.75	0.87	1.00	1.06	1.12	1.17
Dew point : 10℃	2	5	> 10				
B. Correction factor	0.65	0.85	1.00				
Power source frequency : 60Hz	50	60					
C. Correction factor	0.83	1.00					
Ambient temperature: 38℃	42	40	< 38				
D. Correction factor	0.90	0.95	1.00				
Inlet temperature: 60℃	80	70	< 60				
E. Correction factor	0.88	0.94	1.00				

Formula

- Actual capacity =
M2E capacity × (A×B×C×D×E)
- Corrected capacity =
Demanded capacity ÷ (A×B×C×D×E)

Specification

Model	M2E-125S	M2E-150S	M2E-175S	M2E-200S	M2E-250S
Max. capacity (Nm ³ /min)	18	22	27	30	36
Connection (inch)	3"FL	3"FL	3"FL	3"FL	4"FL
Power supply	3 φ /380V(220V,440V Optional)				
Ref. comp. (Kw)	3.6	4.2	4.7	6.5	7.0
Operating current (A)	5.0	6.4	7.6	9.8	10.2
Full-load current (A)	5.7	7.3	8.6	11.0	12.2
Refrigerant	R-407C (R22 · R404A · R134a Optional)				
Fan motor (W)	600	600	600	600	250×2
Dimension	W:780 L:1280 H:1420			W:950 L:1800 H:1600	
Net weight (kg) N Type	270	280	290	300	400
Net weight (kg) G Type	300	310	320	330	400
Operating scope	<ul style="list-style-type: none"> ■ Inlet temp. : N type 5~50℃ (@40℃) G type 5~80℃ (@60℃) ■ Cooling water volume : N type 100 × capacity (L/hr) G type 250 × capacity (L/hr) ■ Ambient temp. : 2~42℃ (@38℃) ■ Working pressure : <1.0 MPa (@0.7 MPa) ■ Dew point : 2~10℃ (@10℃) ■ Cooling water pressure : 0.2~0.4 MPa ■ Cooling water temp. : 5~40℃ (@32℃) 				
Remarks	<ul style="list-style-type: none"> ■ Design condition@60Hz : 1.Ref. comp.(kw) : @ET10℃ · CT54℃ 2.Operating current (A) : @ET5℃ · CT45℃ 3.Full-load current (A) : @ET10℃ · CT54℃ 				
Optional specifications	<ul style="list-style-type: none"> ■ Normal inlet temp. (Without pre-cooler) N type ex:M2E-150SN ■ High inlet temp. (With pre-cooler) G type ex:M2E-150SG ■ Stainless steel pressure vessel (Except condenser & cooler) P type ex:M2E-150SGP ■ Water cooled W type ex:M2E-150SNW ■ PLC control panel PLC type ex:M2E-150SG-PLC ■ High pressure type (Except high inlet temp.) H type ex:M2E-150SNH(1.1~5.0 Mpa) ■ Accessories: Inlet/Outlet pressure gauge, dew point meter, electric auto drain, flow meter. etc 				